





## CASE SIZE OF STANDARD PRODUCTS $D\varnothing \geq 6\text{mm}$ with Safety Vent at Can Bottom

CAP. ( $\mu\text{F}$ )	RATED VOLTAGE WV											
	160		200		250		350		400		450	
	Size	Ripple	Size	Ripple	Size	Ripple	Size	Ripple	Size	Ripple	Size	Ripple
1									8 x 11	60		
									10 x 12	70		
1.5									10 x 12	30		
									10 x 12	30		
1.8									10 x 12	35		
									10 x 12	35		
2.2									10 x 12	40		
									10 x 12	140		
3.3									10 x 12	150		
									10 x 12	180		
4.7					10 x 12	100	10 x 15	55	10 x 15	20	10 x 19.5	220
5.6							10 x 15	58	10 x 15	250	10 x 19.5	250
6.8							10 x 19.5	65	10 x 15	280	10 x 19.5	280
10	10 x 15	320	10 x 15	320	10 x 15	320	10 x 19.5	350	10 x 15	64	13 x 20	450
									10 x 19.5	120		
									13 x 25	200		
15									13 x 20	550	13 x 25	600
22	10 x 19.5	500	10 x 19	233	10 x 19.5	500	13 x 20	650	12 x 25	190		
									13 x 20	225		
									13 x 25	225		
									16 x 25	300		
33	13 x 20	315	13 x 20	366	13 x 20	800			16 x 20	360	16 x 25	980
			10 x 19	366					16 x 25	400		
									16 x 32	437		
47	13 x 25	420	13 x 25	400	16 x 25	500			13 x 30	370	18 x 25	1200
			13 x 20	400					16 x 25	450		
									18 x 25	470		
									18 x 32	538		
68	13 x 20	1180	13 x 25	600			18 x 25	1470	13 x 40	480		
									18 x 25	480		
82							18 x 40	380	16 x 32	520		
									18 x 32	520		
100	13 x 25	1420	16 x 32	800	16 x 25	1530			18 x 32	580		
	16 x 20	1420							16 x 36	540		
120									18 x 32	670		
									18 x 36	670		
150	16 x 25	1890	16 x 36	800	18 x 40	750			18 x 36	770		
220	18 x 25	2370	16 x 36	933								

Note : \* 1. D x L : mm

\* 2. Ripple Current : (mA r.m.s 105°C / 100KHz), ESR (  $M\Omega$  Max25°C / 100KHz)